

Downlight LED de techo Belur



Referencia	201000043	201000044	201000045
Descripción	Downlight LED de techo Belur	Downlight LED de techo Belur	Downlight LED de techo Belur
Potencia	18W	18W	18W
Lúmenes (360°)	1850Lm	1850Lm	1850Lm
Ángulo apertura	120°	120°	120°
Temperatura (K)	3000K / Luz cálida	4000K / Luz día	6500K / Luz fría
Temperatura de trabajo	-10°C / +40°C	-10°C / +40°C	-10°C / +40°C
Tiempo de encendido	<0.5s	<0.5s	<0.5s
Luz completa inmediata	100%	100%	100%
CRI (Ra)	≥80	≥80	≥80
Hg	0.0	0.0	0.0
mA	175mA	175mA	175mA
On / Off	12.500	12.500	12.500
IP	IP20	IP20	IP20
Horas de vida	25.000h.	25.000h.	25.000h.
Voltaje	220-240V	220-240V	220-240V
Hz	50/60Hz	50/60Hz	50/60Hz
Dimensión (ØxH)	Ø225x23mm	Ø225x23mm	Ø225x23mm
Empotramiento (EØxC)	Ø195x210mm	Ø195x210mm	Ø195x210mm
Embalaje	20	20	20

Beneficios: reduce el consumo, el mantenimiento, no parpadea, protege el medio ambiente, no contiene mercurio.

Aplicaciones: casas, hoteles, restaurantes, supermercados, oficinas, negocios, bares.

